Chainbelt Conveyors

Marathon's line of Chainbelt Conveyors is a combination belt that has a chain edged conveyor belt. They are used for medium to high volume applications and feature heavy duty construction, shipped in 2 sections for fast and easy installation, and are fully guarded on 3 sides.

B Class Chainbelt Conveyors used for used for medium volume (5 to 10 tons/hour) baler feed and MRF line feed applications up to 5 ft. wide. These conveyors are ideal for a variety of applications such as MRF sorting line feeds, large Side-Eject balers, open-end Auto-Tie balers, and small Two-Ram balers. Features include: economical 2.6" millchain, 5 to 10 hp motors, 2 ply rubber belt (3 ply optional), tapered roller bearings, and pit covers. Also available with variable speed controls.

A Class Chainbelt


for medium-high volume (12 to 20 tons/hour) for heavier duty applications, long pits, and up to 6 ft.

wide belts. These conveyors are ideal for a variety of applications such as large open-end Auto-Tie balers, large Two-Ram balers, mixed waste lines, and MRF sorting line feeds. Features include: strong 4" pitch millchain, 7.5 to 15 hp motors, up to 50 ft. long pits, 3 ply rubber belt, tapered roller bearings, pit covers, and variable speed controls.

waste handling, recycling and reduction equipment

AR Class Chainbelt Conveyors for high volume (20 to 30 tons/hour), heavy-duty applications, very long pits, and up to 7 ft. wide belts. These conveyors are ideal for a variety of applications such as large openend Auto-Tie balers, large Two-Ram balers, mixed waste lines, and MRF sorting line feeds. Features include: flanged wheel with 6" and 9" pitch engineered chain, 10 to 20 hp motors, up to 100 ft. long pits, 3 ply rubber belt, tapered roller bearings, pit covers, and variable speed controls.





Product Class	Application	Width up to:	Shaft Elev.	Pit Length	Config.	Note:
В	Medium volume (5 to 10 tph)	5 ft.	up to 13 ft.	up to 15 ft.	BG	Variable Speed Control (VS) optional Optional Above Grade configuration
A	Medium high volume (12 to 20 tph)	6 ft.	up to 20 ft.	up to 50 ft.	BG	Variable Speed Controls standard
AR	High volume (20 to 30 tph)	7 ft.	up to 20 ft.	up to 120 ft.	BG	Variable Speed Controls standard



Marathon Equipment is your single source for conveyors, waste compaction systems, recycling equipment and reduction equipment!









